

CA8DL and CA4T4DL are compact monitors for displaying digital signals and conditions via the programmable LEDs. Additional functions and events can be triggered comfortably with CA4T4DL by just pressing push buttons. The high-speed CAN interface guarantees a reliable and fast communication with the data logger.

Technical Data	
CA8DL	8 programmable, three-colored LEDs (red, green, orange), dimmable
CA4T4DL	1 event push button (red) 3 miniature push buttons 4 programmable, three-colored LEDs (red, green, orange), dimmable
Interface	1 high-speed CAN bus
Terminator	120 Ohm, on/off switchable via jumper
Operating voltage	+5 V ... +30 V
Current consumption	<ul style="list-style-type: none"> • CA8DL typ. 11 mA (all LEDs off) typ. 55 mA (all LEDs green, 100 %) typ. 55 mA (all LEDs red, 100 %) typ. 99 mA (all LEDs orange, 100 %) • CA4T4DL typ. 10 mA (all LEDs off) typ. 34 mA (all LEDs green, 100 %) typ. 34 mA (all LEDs red, 100 %) typ. 58 mA (all LEDs orange, 100 %)
Operating temperature range	-40 °C ... +80 °C

Housing	
Material	ABS (Acrylnitril-Butadien-Styrol)
Maße (LxBxH)	80 x 40 x 20 mm
Gewicht	~ 50 g

