

CAS1T3L/CASM2T3L



Discover our products online!

- › CASM2T3L: Voice recording with date and time, and an additional programmable button
- › Ideal design to house it in the cup holder of a vehicle
- › Programmable push button
- › 3 programmable LEDs
- › Acoustic signal (beeper)

Triggering Events

CAS1T3L and CASM2T3L are compact monitors for displaying digital signals and conditions via the programmable LEDs and events can be triggered by just pressing push buttons.

Additionally, the CASM2T3L can be used to document observations in audio form during the recording, which can be later matched with the events. The round design enables an installation in a cup holder.

CAS1T3L/CASM2T3L

Technical Specifications

Technical Data

CAS1T3L
3 Programmable LEDs, red, green and yellow
1 Event push button (red)
1 Controllable acoustic signal (beeper)

CASM2T3L
3 Programmable LEDs red, green and yellow
1 Event push button (red)
1 Controllable acoustic signal (beeper)
1 Push button for audio recording
1 Microphone

Interface 1 High speed CAN

Operating Voltage +5 V (via the AUX interface of the G.i.N data logger)

Current Consumption

- CAS1T3L Typ. 120 mA
- CASM2T3L Typ. 115 mA

Operating Temperature Range -30 °C ... +60 °C

Housing

Material PVC

Dimensions (ØxH) 63 mm, 39 mm

Weight ~ 267 g

